

AMENDMENTS TO THE CLAIMS

The following is a complete, marked up listing of revised claims with a status identifier in parentheses, underlined text indicating insertions, and strikethrough and/or double-bracketed text indicating deletions.

LISTING OF CLAIMS

1. (Currently Amended) A protective switching device comprising:
an operating switching device configured to switch a load on and off;
a disconnection device on an exterior surface of the protective switching device, the
disconnection device being configured- to disconnect an input terminal from an output
terminal, connectable to the appliance to be driven; and
a protective device configured to protect the appliance to be driven against short circuits,
the protective device including at least one fuse in each phase for disconnection in the event
of a short circuit, with the operating switching device, the disconnection device and the
protective device being connected in series and being integrated in a housing, wherein the at
least one fuse is in the form of a semiconductor protective fuse and the disconnection device
includes two disconnection points.
2. (Cancelled)
3. (Previously Presented) The protective switching device as claimed in claim 1, wherein
the at least one fuse is removable from the housing.
4. (Cancelled)
5. (Currently Amended) The protective switching device as claimed in claim 1, wherein the
protective device is arranged between the disconnection device and ~~an~~ the output terminal to the
appliance to be driven.

6. (Previously Presented) The protective switching device as claimed in claim 1, wherein the disconnection device, when in the open state, disconnects and releases the at least one fuse from at least one contact, for removal.
7. (Previously Presented) The protective switching device as claimed in claim 1, further comprising at least one of a rotary and slide mechanism for opening and closing the disconnection device.
8. (Previously Presented) The protective switching device as claimed in claim 1, wherein the at least one fuse is in the form of a cylindrical fuse.
9. (Previously Presented) The protective switching device as claimed in claim 1, wherein the disconnection device includes the functionality of a fused load disconnecter.
10. (Cancelled)
11. (Previously Presented) The protective switching device as claimed in claim 1, wherein the at least one fuse is arranged in a moving part of the disconnection device.
12. (Previously Presented) The protective switching device as claimed in claim 1, further comprising a monitoring device for recording of tripping of the at least one fuse.
13. (Previously Presented) The protective switching device as claimed in claim 1, wherein electronic switching points are bridgeable by mechanical contacts.
14. (Currently Amended) The protective switching device as claimed in claim 1, further comprising an overload device arranged in series with the operating switch device, the disconnection device and the protective device, and between the switching device and the appliance.

15. (Previously Presented) The protective switching apparatus as claimed in claim 14, wherein the overload device includes an overload relay.
16. (Cancelled)
17. (Previously Presented) The protective switching device as claimed in claim 21, wherein the at least one fuse is removable from the housing.
18. (Cancelled)
19. (Currently Amended) A protective switching device comprising:
means for switching a load on and off;
means for disconnecting an input terminal from an output terminal, the means for disconnecting being on an exterior surface of the protective switching device and being connectable to the appliance to be driven; and
means for protecting the appliance to be driven against short circuits, the means for protecting including means, in each phase, for disconnecting in the event of a short circuit, with the means for switching, the means for disconnecting and the means for protecting being connected in series and being integrated in a housing, wherein the means for protecting is replaceable only when the means for disconnecting is in an open state, wherein the at least one fuse is in the form of a semiconductor protective fuse and the disconnection device includes two disconnection points.
20. (Previously Presented) The protective switching device as claimed in claim 19, wherein the means, in each phase, for disconnecting in the event of a short circuit includes a fuse in each phase, at least one fuse being removable from the housing.
21. (Currently Amended) The protective switching device as claimed in claim 1, wherein the protective switching device is in the form of at least one of a semiconductor motor controller, a semiconductor contactor and an electromechanical switching device.

22. (Currently Amended) The protective switching device as claimed in claim 1, further including input terminals and output terminals on an exterior of the housing of the protective switching device.

23. (Currently Amended) The protective switching device as claimed in claim 11, further including a handle on an exterior of the housing of the protective switching device, the handle being connected to the moving part.

24. (New) The protective switching device as claimed in claim 22, wherein the input terminals and output terminals are on a same exterior surface of the housing.